

Getting to Know the Britax ClickTight Convertible Car Seats



Getting to Know the Britax ClickTight Convertible Car Seats

- ❑ When you have completed this Continuing Education Unit session you will:
 - Have an understanding of the product features that the ClickTight Convertible Car Seats include.
 - Be familiar with the weight, height and age requirements for the ClickTight Convertible Car Seats including use of the CLICKTIGHT Installation System.
 - Have a general understanding of the installation of ClickTight Convertible Car Seats rear-facing.
 - Have a general understanding of the installation of ClickTight Convertible Car Seats forward-facing.
- ❑ For this CEU opportunity, you must answer **16** out of **20** questions correctly in order to get the one (1) CEU awarded. If you incorrectly answer more than **4** questions, then you may review the material again and retake the quiz.
- ❑ Much of the information in this CEU material can be found at us.britax.com and in the user guides for each model.

ClickTight Installation Technology



Step 1

Open

Quick, easy access to belt path



Step 2

Buckle

Installs simply with just the vehicle seat belt



Step 3

Close

Built-in seat belt tensioner eliminates installation struggle

How to open ClickTight

[CLICK HERE](#) for How To Open CLICKTIGHT Panel Video



1. Identify the ClickTight Key. Find the indentation.



2. Place your finger on the indentation and push forward.



3. Hold the ClickTight Key with both fingers and rotate clockwise to unlock.



4. Lift the front panel of the seat to reveal the belt path.

Reminders with CLICKTIGHT Installation Technology

1

CLICKTIGHT does not require any pushing or pulling to tension the vehicle belt or compress the vehicle seat.

2

Installation with a vehicle seat belt is preferred / recommended over lower connectors.

3

It is a LOCK-OFF.
User Guide does not instruct to switch retractor w/ Lap-shoulder belts.

4

ALWAYS release vehicle buckle BEFORE opening CLICKTIGHT when removing from vehicle.

Marathon ClickTight



MOD BLUE



MOD IVORY



MOD PURPLE



MOD BLACK

5-40 lbs. Rear-Facing | 20-65 lbs. Forward-Facing | 49" Standing Height

(14) Harness slots: 8.35 to 19.4

Lower Connector (max child weight): 35 lbs. Rear-Facing | 40 lbs. Forward-Facing

Expiration: 10 Years from DOM

Boulevard ClickTight



GRAY CONTOUR



BLUE CONTOUR



PURPLE CONTOUR



GREEN CONTOUR



BLACK CONTOUR

5-40 lbs. RF | 20-65 lbs. FF | 49" Standing Height

(14) Harness slots: 8.35 to 19.4

Lower Connector (max child weight): 35 lbs. Rear-Facing | 40 lbs. Forward-Facing

Expiration: 10 Years from DOM

Advocate ClickTight



GRAY OMBRE



BLUE OMBRE



PURPLE OMBRE



GREEN OMBRE



BLACK OMBRE

5-40 lbs. RF | 20-65 lbs. FF | 49" Standing Height

(14) Harness slots: 8.35 to 19.4

Lower Connector (max child weight): 30 lbs. Rear-Facing | 35 lbs. Forward-Facing

Expiration: 10 Years from DOM

ClickTight Convertible Features

Grows With Your Child

Infant & Toddler
5-40 LBS | 2.3-18 KG



Preschool
20-65 LBS | 9.1-29.4 KG



14
positions



Quick-Adjust Headrest & Harness
move together to create the perfect fit



Side Impact
Protection



Steel
Reinforced
Frame



7-Position
Recline

Easy-Read
Level Indicator

ClickTight Convertible Features



CLICKTIGHT Convertibles have 7 recline positions. To adjust the recline position; Pull the recline handle then rotate the child seat shell until the ball in the recline indicator is in the allowable section for the child.


Using the Recline Indicator



NOTE: Set the seat position **BEFORE** installing.

Rear-Facing

In rear-facing installations it is important that the child seat be reclined to maintain proper head and neck control with smaller infants. Use the recline indicator on the child seat to help achieve an acceptable recline angle, with the ball in the recline indicator in the allowable blue section for the size of the child. If necessary, the proper recline angle can be achieved by placing a rolled towel or pool noodle in the vehicle seat bight.




Infants and children with no head and neck control – recline indicator ball **MUST BE** in the light blue section

Older children (toddlers) with proper head and neck control – recline indicator ball **CAN BE** in light blue or dark blue.

NOTE: If necessary, the proper recline angle can be achieved by placing a rolled towel or pool noodle in the vehicle seat bight.

Adjusting the Harness Length



ClickTight Convertible Car Seat: Harness Hip Adjustment - Standard Position


Before installing and using your ClickTight convertible, ensure that the harness is properly adjusted and secured in the standard position at the hip.

ClickTight Convertibles are shipped with the hip adjustment in the longer/extra room position.

IMPORTANT: Adjust the harness to the shortened length if a snug harness cannot be achieved with a small infant (approx. 10 lbs. and under).

Reflected in user guides August 2017

This can be applied retroactively.



ClickTight Convertible Car Seat: Harness Hip Adjustment - For Extra Room

Before installing and using your ClickTight convertible, ensure that the harness is properly adjusted and secured in the standard position at the hip.

[CLICK HERE](#) to change from long/extra room to Shortened/Standard Position Standard Position

[CLICK HERE](#) to change from Shortened/Standard Position to the long/extra room length

Child Fitment – Advocate & Boulevard

Rear Facing: 5 – 40 lbs (2.3 – 18 kg)

Britax strongly recommends that children ride rear facing to the highest weight or height specified.

Use rear facing:

- with harness straps in the closest position at or below the child's shoulders **and**
- with children who weigh 5 – 40 lbs (2.3 – 18 kg) **and**
- when the top of the child's head is at least 1 in. (2.5 cm) below the top of the head restraint.




Britax strongly recommends that children ride rear facing to the highest weight or height specified.

Forward Facing: 20 – 65 lbs (9.1 – 29.4 kg)

Britax strongly recommends that children should be secured with a harness system until they exceed the weight or height limits specified.

Use forward facing:

- with harness straps in the closest position at or above the child's shoulders, parallel to level ground **and**
- with children who weigh 20 – 65 lbs (9.1 – 29.4 kg) **and**
- who are 49 in. (124.5 cm) or less in height **and**
- when the top of the ears are below the top of the head restraint.



Britax strongly recommends that children should be secured with a harness system until they exceed the weight or height limits specified.


Child Fitment – Marathon

Rear Facing: 5 – 40 lbs (2.3 – 18 kg)

Britax strongly recommends that children ride rear facing to the highest weight or height specified.

Use rear facing:

- with harness straps in the closest position at or below the child's shoulders **and**
- with children who weigh 5 – 40 lbs (2.3 – 18 kg) **and**
- when the top of the child's head is at least 1 in. (2.5 cm) below the top of the head pad.



Britax strongly recommends that children ride rear facing to the highest weight or height specified.




Forward Facing: 20 – 65 lbs (9.1 – 29.4 kg)

Britax strongly recommends that children should be secured with a harness system until they exceed the weight or height limits specified.


Use forward facing:

- with harness straps in the closest position at or above the child's shoulders, parallel to level ground **and**
- with children who weigh 20 – 65 lbs (9.1 – 29.4 kg) **and**
- who are 49 in. (124.5 cm) or less in height **and**
- when the top of the ears are below the top of the head pad.



Britax strongly recommends that children should be secured with a harness system until they exceed the weight or height limits specified.

Positioning the Buckle



The child seat shell contains an inner buckle slot and an outer buckle slot. Position the buckle in the slot closest to but not under the child.

Are the Impact Absorbing Chest pads required on CT convertibles?



Securing Your Child

IMPORTANT: Impact absorbing chest pads are highly recommended for forward-facing mode. Removal of chest pads is optional for rear-facing mode to ensure a snug fit for small infants.

Select models of CLICKTIGHT convertibles do not come with chest pads.
(typically black shells)

This slide pertains specifically to CLICKTIGHT convertibles.

Positioning BRITAX in BPB mode with Lower Anchors



The Britax belt-positioning booster seats can be positioned on the vehicle seat using the lower anchor system. Use the vehicle's lap-shoulder belt to secure the child. Ensure that the lower anchors do not interfere with the vehicle belt function and alignment when securing the child.
Example shown: Offset lower anchors cannot be used to secure a Britax belt-positioning booster because the lap-shoulder will not properly position on the child.

Use of LATCH with ClickTight Convertibles

❑ LAP-SHOULDER SEAT BELT INSTALLATIONS ARE PREFERRED.


❑ If / when installed with LATCH:

➤ **ADVOCATE ONLY:**

- REAR-FACING: Do NOT install by this method for a child weighing more than 30 lbs.
- FORWARD-FACING: Do NOT install by this method for a child weighing more than 35 lbs.

➤ **BOULEVARD & MARATHON ONLY:**

- REAR-FACING: Do NOT install by this method for a child weighing more than 35 lbs.
- FORWARD-FACING: Do NOT install by this method for a child weighing more than 40 lbs.





Example shown from Advocate ClickTight

Where is the serial number and manufacture date on ClickTight Convertibles?



Tether attached during a crash?




This is one indicator the seat should be replaced.

Can a Britax car seat be installed in the center seating position borrowing the inner anchors (LATCH) of the outboard seating positions?

No. To use lower anchors / LATCH, it must be a designated LATCH position by the vehicle with standard spacing.

Using Lower Anchors and Tethers for Children (LATCH)




The Lower Anchors and Tethers for Children or LATCH, is a system available on this child seat that offers an alternative to vehicle seat belt installation methods. The figure above shows typical locations for lower anchors and tether anchors in a vehicle. See pages 2-3 for LATCH components on this child seat.

Check your vehicle owner's manual to learn if it is equipped with LATCH, the maximum weight rating for the lower anchors, tether anchors capacities, and information on the lower anchor locations and designated seating positions available for use with this child seat.



How much overhang is acceptable with the ClickTight Convertibles?



Ensure that the base of the child seat is flat on the vehicle seat and no more than 3 in. (7.5 cm) of the base hangs over the edge of the vehicle seat

When do ClickTight Convertibles expire?

NOTES:

- Britax strongly recommends that children should remain in a child seat with a 5-point harness until reaching the maximum weight or height allowed.
- To prevent injury due to deterioration or hidden damage, discontinue use of this child restraint if it is older than ten (10) years. See the Serial Number and Manufactured Date Label on the child restraint.
- Before each use, check this child restraint and its components to make sure they are in good condition and good working order.
- Discontinue use of this child restraint if it has been in a moderate or severe crash. It is not necessary to replace a child restraint after a **minor** crash, defined by the US National Highway Traffic Safety Administration (NHTSA) as:
 - a. The vehicle is drivable from the crash site; **and**
 - b. The vehicle door nearest to the child restraint was not damaged; **and**
 - c. No vehicle occupants were injured; **and**
 - d. There is no visible damage to the child restraint; **and**
 - e. The airbags (if present) did not deploy.

The statement for number of years will be found in the Warnings / Note section of user guide.

For newer models, it can also be found on the serial number label.



XXXXXXXXXXXXXXXXXXXXX

MODEL: XXXXXXXXXXXXX

BATCH/LOTE: XXXXXXXXXX

SERIAL/SERIE: XXXXXXXXXXXXX

EXPIRES/EXPIRS: 09/31/2024

MANUFACTURED BY/FABRICADOS POR:
BRITAX CHILD SAFETY, INC.
4140 PLEASANT RD. FORT MILL, SC 29708 USA


MANUFACTURED
FABRICADOS:
09 | 2018
MO/MES | YR/AÑO

Installation of a ClickTight Convertible car seat when vehicle head restraint causes interference.

Vehicle Headrest

! WARNING!

In some cases, the vehicle headrest can prevent the child restraint headrest from being raised high enough to properly adjust the harness for the fit of your child when using a forward-facing reclined position. **DO NOT** force the child restraint headrest past the vehicle headrest.



Doing so could cause the child restraint not to perform as intended. If the location of the vehicle headrest interferes with the child restraint headrest, raise or remove the vehicle headrest. If the vehicle headrest can not be removed, move the child restraint to the upright position or try a different seating location.

Inflatable Seat Belt Policy

Can Britax car seats and booster seats be installed with inflatable seat belts?

No. Current models being manufactured cannot. Some discontinued models can.

The Inflatable Seat Belt Policy can be found at

<https://us.britax.com/support/frequently-asked-questions>



How do I clean my soft goods (covers)?


- ONLY SafeWash covers by Britax are machine washable and machine dryable.
- USER GUIDE Cleaning Instructions:
 - Refer to product care label for wash instructions.
 - If care label indicates machine washable, always refer to us.britax.com/faqs for important care information.




Naturally flame-retardant knit is safe to machine wash and dry.

Care Instructions
Instructions d'Entretien
Instrucciones de Cuidado


Machine wash cold, delicate cycle with mild soap

 Laver à la machine à l'eau froide, cycle délicat avec savon doux
Lave a máquina con agua fría, ciclo de ropa fina con jabón suave


Tumble dry low

 Sécher à la machine cycle doux
Secar a temperatura baja


DO NOT iron

 NE PAS repasser
NO planchar

DO NOT bleach

 NE PAS javeliser
NO utilizar lejía


DO NOT dry clean

 NE PAS faire nettoyer à sec
NO limpiar en seco


P11250400_A:08.18

Care Instructions
Instructions d'Entretien
Instrucciones de Cuidado


Hand wash with mild soap

 Laves à main à l'eau froide et savon doux
Lavar a mano en agua fría con jabón suave


Line dry

 Séchez sur corde à linge
Colgar para secar


DO NOT iron

 NE PAS repasser
NO planchar


DO NOT bleach

 NE PAS javeliser
NO utilizar lejía

DO NOT dry clean

 NE PAS faire nettoyer à sec
NO limpiar en seco


DO NOT machine dry

 NE PAS mettre dans une sécheuse
NO secar en secadora

P256900_R3:07.13

Crotch Rolls & Side Rolls

ANSWER:



BRITAX rear-facing only and convertible car seats provide positioning inserts with the car seat. As well, offer multiple crotch buckle positions to assist in properly positioning and securing the child in the harness system.

If the positioning insert provided with the BRITAX car seat does not position the child as needed, it is acceptable to place a rolled receiving blanket on each side of the child for lateral support – once the child is properly secured within the harness as instructed in the user guide. The rolled receiving blankets should not be placed between the child and the harness.

It is **not** acceptable to use a crotch roll with any BRITAX car seat to position a child.

Coats | Heavy Clothing



BULKY COAT



LOOSE HARNESS

The following is in each BRITAX user guide in "Securing the Child".

IMPORTANT: Remove bulky coats and/ or jackets before putting the child in the car seat.

- Some suggestions would be:
 - Preheat car.
 - Put jacket on backwards after child is secured in harness.
 - The B-WARM can be used with any Britax rear-facing only seat.



Accessories and Britax Products

(seat protectors, infant inserts, etc.)



The use of non-Britax covers, inserts, toys, accessories or tightening devices is not approved by Britax. Their use could cause this child restraint not to perform as intended in a crash.



We do not currently approve of any other accessories or seat coverings to use in place of the Britax vehicle seat protector.

Replacement after a Motor Vehicle Crash

Discontinue use of this child seat if it has been in a moderate or severe crash. It is not necessary to replace a car seat after a minor crash, defined by the US National Highway Traffic Safety Administration (NHTSA) as:

- a. The vehicle is drivable from the crash site; and
- b. The vehicle door nearest the child seat was not damaged; and
- c. No vehicle occupants were injured; and
- d. There is no visible damage to the child seat; and
- e. The airbags (if present) did not deploy



This information can be found in each Britax product user guide in the WARNINGS or IMPORTANT NOTES section as well as an FAQ on our website <https://us.britax.com/support/frequently-asked-questions/after-a-car-crash>.

Use of ClickTight Convertibles on Aircraft

Make sure your car seats is approved for use on aircraft. Look for statement on label:

- This restraint is certified for use in motor vehicles and aircraft.

Best practice is EVERY family member has a seat and is properly secured (seat belt or car seat. While the FAA allows children under the age of 2 to be held on lap, remember – turbulences are unexpected at any time.

Call airlines and ask if there are discounts for seats for children flying during non-popular times or flights.

By bringing YOUR car seat with you – you do not have to worry about renting a car seat from a car rental agency.

⚠ WARNING!

DEATH or SERIOUS INJURY can occur.

- Use only in a rear-facing position when using it with an infant weighing less than 20 pounds (9.1 kg).
- Use only with children who weigh between 5 and 65 pounds (2.3 and 29.4 kg) and with a height of 49 inches (124.5 cm) or less. Rear-facing for children weighing between 5 and 40 pounds (2.3 and 18 kg) and forward-facing for children weighing between 20 and 65 pounds (9.1 and 29.4 kg).
- Snugly adjust the belts provided with this child restraint around your child.
- Secure the top anchorage strap provided with this child restraint.
- Secure this child restraint with the vehicle's child restraint anchorage system if available or with a vehicle belt.
- Follow all instructions on this child restraint and in the written instructions located in the pocket behind the cover.
- Register your child restraint with the manufacturer.
- This child restraint system conforms to all applicable Federal motor vehicle safety standards. **This Restraint is Certified for Use in Motor Vehicles and Aircraft.**

P02085500_A:08.14

Encourage Product registration

IMPORTANTE

En caso de una retirada, sólo podemos comunicarnos con usted si tenemos su nombre y dirección. Usted **DEBE** enviar la tarjeta adjunta o registrarse en línea para estar en nuestra lista para productos con avisos de retiro del mercado a causa de defectos.

Nosotros ya hemos pagado el envío.

Hágalo hoy.

IMPORTANT

In case of a recall, we can reach you only if we have your name and address. You **MUST** send in the attached card or register online to be on our recall list.

We've already paid the postage.

Do it today.



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL

FIRST-CLASS MAIL PERMIT NO. 1062 CHARLOTTE, NC

POSTAGE WILL BE PAID BY ADDRESSEE

BRITAX CHILD SAFETY INC
PO BOX 91167
ALLEN TOWN PA 18109-9925



PARA LA SEGURIDAD DE SU NIÑO

Por favor, tómese unos momentos para llenar y devolver la tarjeta adjunta o registre en línea a través del enlace directo a la página web del fabricante.

Aunque los asientos de seguridad para niños se someten a pruebas y evaluación, es posible que un asiento de seguridad para niños podría ser retirado del mercado.

En caso de una retirada, sólo podemos comunicarnos con usted si tenemos su nombre y dirección, así que por favor envíe la tarjeta o registre en línea para estar en nuestra lista de productos con avisos de retiro del mercado a causa de defectos.

Por favor, llene su tarjeta y envíela AHORA, o registre en línea en www.BritaxUSA.com/registration mientras que usted está pensando en ello.

La tarjeta ya está dirigida a Britax y hemos pagado los gastos de envío.

FOR YOUR CHILD'S CONTINUED SAFETY

Please take a few moments to promptly fill out and return the attached card or register online using the direct link to the manufacturer's website provided.

Although child restraint systems undergo testing and evaluation, it is possible that a child restraint could be recalled.

In case of recall, we can reach you only if we have your name and address, so please send in the card or register online to be on our recall list.

Please fill this card out and mail it NOW, or register online at www.BritaxUSA.com/registration, while you are thinking about it.

The card is already addressed and we've paid the postage.

Tear here / Desgano aquí.

Consumer: Just fill in your name and address and e-mail address (optional)

Consumidor: Sólo tienes que escribir tu nombre y dirección y dirección de correo electrónico (opcional)

Name/Nombre

Address/Dirección

City/Ciudad

State/Estado

Zip/Código Postal

Country/País

E-mail/Correo electrónico
(optional/opcional)

CHILD RESTRAINT REGISTRATION CARD
TARJETA DE REGISTRO PARA ASIENTOS DE SEGURIDAD PARA NIÑOS

R3:04.13

P478800

- Visit the manufacturers website
- Safety Notices
 - <https://www.nhtsa.gov/recalls>
 - <https://us.Britax.com/support/safety-notices-recalls>
- Register CRS
 - Reassure caregivers manufacturers cannot use their contact information for any reason other than to contact them in the event of a Safety Notice.
 - Mailing registration card
 - On-line
 - Call car seat manufacturer Customer Service
 - Number in user guide, label on car seat
 - <https://us.britax.com/support/register-product>

Additional Resources: Installation Videos

- ❑ [CLICK HERE](#) for ClickTight Convertible Installation Videos
- ❑ [CLICK HERE](#) for How to Properly Attach Harness Straps to Yoke
- ❑ Rear-Facing Installation
 - [CLICK HERE](#) for Lower Anchor Installation
 - [CLICK HERE](#) for Lower Anchor Installation and Anti-Rebound Bar
 - [CLICK HERE](#) for Lap-Shoulder Belt Installation and Anti-Rebound Bar
 - [CLICK HERE](#) for Lap-Shoulder Belt Installation
- ❑ Forward-Facing Installation
 - [CLICK HERE](#) for LATCH Installation
 - [CLICK HERE](#) for Lap-Shoulder Belt Installation

Additional Resources



Installation Videos (YouTube Channel)

<http://youtube.com/BritaxUSACarSeats>



Access the current BRITAX product user guides

<https://us.britax.com/support/instructional-videos-and-user-manuals>



To determine lower anchor and/or tether capacity use by vehicle make.

[VM-LATCH-Anchor-Weight-Limits-2019-11.pdf \(cpsboard.org\)](#)

Assisting Caregivers

Customer Service

<https://us.britax.com/support/frequently-asked-questions>

Britax products ONLY:

Trouble Shooting Assistance

Call: 888-427-4829

Monday to Thursday
9:00 am – 5:15 pm (ET)

Friday 9:00 am – 4:45 pm (ET)

Submit Email:

<https://us.britax.com/support/contact-us>

Schedule a Virtual Appointment:

<https://britaxtest.appointlet.com/>

Seat Checks

- <https://us.britax.com/press/events>
- Any brand car seat
- Virtual appointments
- In-Person Seat Checks by appointment
- In-Person Seat Check Event Dates

Technician Discounts

- ❑ Yes, we offer discounts to currently certified Technicians and Instructors for personal use.
 - Two products can be purchased per calendar year.
- ❑ U.S. certified seats shipped to a continental U.S. address – Alaska and Hawaii not included.
- ❑ Please email sarah.tilton@britax.com a PDF of your current wallet card.
 - You can access this through your certification profile at cert.safekids.org. Safe Kids includes a nice [How to Print a Wallet Card](#) if you are not familiar on how to access this.
- ❑ Once I receive your current certification wallet card via email, I will reply providing a current order form including pricing and instructions.

Sarah Tilton, CPST-I

Director, Consumer Advocacy

Thank you!

Product Assistance as Technician/Instructor:



Email: Sarah.Tilton@Britax.com



Phone: (704) 409-1695



<https://www.facebook.com/CarSeatTutor>




[carseat_tutor](https://www.instagram.com/carseat_tutor)



Thank you for learning more about BRITAX!

- **RECOMMENDED:** Once you complete the quiz, you will have the option to print (hard copy or create a PDF) a certificate (see below).



- You should also receive an email. If you did not print a copy immediately after completion and do not receive an email regarding your score (a) check your spam/junk folder and (b) consult your IT department that the system will allow emails from wordpress@ceu.britax.com On Behalf Of ceuquiz@britax.com.

Thank you for learning more about BRITAX!

- If you successfully completed the quiz, please save the email or print a copy and save with your recertification documentation.
 - The emails come from wordpress@ceu.britax.com On Behalf Of ceuquiz@britax.com. Certificates/emails of completion cannot be re-created.
- If you did not successfully complete the quiz, please review the material again and retake the quiz when you are ready.