

# Frontier **Rubber Cap Installation**

Instructions

For model #s E9L54E7, E9L54H6, E9L54H7, E9L54M6, E9L5490 Manufactured between April 1 2008 - September 14 and 17, 2008

#### Read all instructions thoroughly before proceeding.

Figure 1 shows materials included in kit

### Replacement Parts Required:

\*Items not shown to scale

- A Rubber caps (qty 2 included with kit)
- B User Guide cover label (qty 1 included with kit)
- C Instruction notes label (qty 1 included with kit)

#### Installing the Rubber Caps

- 1. Remove the child seat from the vehicle and place the child seat on a flat surface.
- Loosen the harness straps by lifting the harness adjuster lever while pulling both harness straps as far forward as possible at the same time (Fig. 2).
- 3. Locate the harness yoke on the back of the child seat (Fig 3).
- 4. From the side, press one rubber cap (item A) over the inside prong of the harness until the cap is fully inserted (Fig 4). Repeat for the remaining rubber cap.
- Your child seat is now ready to be installed in your vehicle. The harness yoke should match figure 5 once the rubber caps have been properly installed.

# **Applying the Labels**

- 1. Remove the paper backing from the user guide cover label (item B) and apply it to the front cover of the user guide (Fig 6).
- 2. Remove the paper backing from the Instruction notes label (item C) and apply it to the inside back cover of the user guide (Fig. 7).

# Removing the Rubber Caps

The rubber caps must be removed when converting your child seat from harness mode to booster mode or when removing the cover for cleaning. Complete the following procedure to remove the rubber caps from the harness yoke.

Lift the edge of the rubber cap and slide it from the inside prong of the harness yoke (fig 8). Repeat to remove the remaining rubber cap.

**IMPORTANT:** Always reinsert the rubber caps when converting your child seat from booster mode to harness mode or replacing the cover after cleaning. Always loosen the harness by pulling both harness straps at the same time. Ensure the harness is properly adjusted and has a comfortable but snug fit around your child every time you use your child seat.















